



Catalogue
CATERING
Chapter
DISHWASHING

Model
CO-502 230V 1N 50Hz

19058149

03/04/2019

CO-502 DISHWASHER


- Front-loading dishwashers - EVO Generation.
 - Constructed in stainless steel.
 - Whole body with double wall.
 - Counterbalanced door with stainless steel hinges and double spring.
 - Furniture which allows the machine to be positioned under 850 mm high work surfaces.
 - Rounded tank to facilitate washing and drainage.
 - Stainless steel armoured heating elements in the wash tank and rinse boiler.
 - Useful internal height of 380 mm. Accepts GN 1/1 trays.
 - 600 W wash pump
 - Boiler with capacity of 7 litres.
 - Magnetic safety stop switch in door opening.
 - Safety thermostat
 - Model with electronic control and control panel and thermostatic filling.
 - 90°, 120° and 180° wash cycles.
 - Theoretical maximum production of 40 baskets/hour.
 - Tank with volume of 20 litres, with 2.8 kW heating element.
- Single-phase Multipower installation, with heating in the boiler which can be selected at time of installation, either 2.8 or 3.7 kW.
- 2.4 litre water consumption per cycle.
 - Rinse with thermostat system. Standard factory setting disabled. Easy to enable.
 - Multi-voltage: Allows the machine to be connected to a single-phase or three-phase voltage network.
 - Double system of filter trays in the tank.
 - IPX4 anti-humidity protection.

Equipment included:

"One CT-10 base basket, 1 CP-16/18 basket for plates and two cutlery holders."

DIMENSIONS

X Width	600 mm	X Gross width	660 mm
Y Depth	600 mm	Y Gross depth	745 mm
Z Height	830 mm	Z Gross height	1030 mm
Net Weight	67,0 kg	Gross Weight	82,0 kg
Net volume	0,299 m3	Gross volume	0,506 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	3,400 kW
Heating power	2,80 kW
Voltage	230V - 1N
Amperage	14,7 A
Electric frequency	50Hz

WATER TECHNICAL SPECIFICATIONS

Pressure	H2O: 200-400kPa(2-4bar)
Water max consumption	54,00 L/h

CONNECTIONS TECHNICAL SPECIFICATIONS

230 V three-phase wiring	3 X 2,5 + T - 25A
Single-phase 230V wiring	2X6 + T - 40 A
Three-phase +N 40V wiring	4X2,5 + T - 20 A
Hot softened water diameter	3/4"
Drain 1 diameter	2"

OTHERS

Noise level	65,00 dB
-------------	----------



Catalogue
CATERING

Chapter
DISHWASHING

Model
CO-502 230V 1N 50Hz

19058149

03/04/2019

