

MODELUX FULL DOOR SERIES

Reach-in, Refrigerator, 38.1 cu.ft., Stainless steel inside and outside, 4" caster, Adjustable shelves, Digital temperature control system, Top mount compressor, 1/3 HP, 115 V / 60 Hz, 220~240 V / 50 & 60 Hz, Auto defrosting system



Technical Features

Drain Pan

Digital temperature control system

Efficient refrigeration system

High-density polyurethane insulation



MSM EQUIPMENT MANUFACTURER SDN BHD

Design Features

Model		MDS-1040R1L	MDS-1040F1L	MDS-1040HRF1L
		Refrigerator	Freezer	Combination
Capacity	liter	1081	1053	1014 Ref : 510 / Fre : 504
	cu. ft.	38	37	36
Exterior Dimension	mm	1260 x 800 x 1830*		
(W x D x H)	inch	49.6 x 31.5 x 72*		
Packing Dimension (W x D x H)	mm	1340 x 885 x 1874		
	inch	52.8 x 34.8 x 73.8		
Net Weight	kg	118	138	146
	lb	262	307	324
Packing Weight	kg	140	160	168
	lb	311	356	373
No. of Casters		4		
No. of Shelves		8		
Door		2 Swing Doors		
Compressor (hp)		1/3	1/3 2EA	1/3 2EA
Refrigerant		R-134A		
Range of Temperature		0~7 °C / 28~39 °F	-24~-3 °C / -11~27 °F	Ref : 0~7°C / 28~39°F Fre : -24~-3°C / -11~27°F
Voltage / Frequency		115 V / 60 Hz 220~240 V / 50 & 60 Hz		
Rated Input (A/W, 115V 60Hz)		4.0 A / 355 W	5.0 A / 480 W	6.5 A / 580 W
Rated Input (A/W, 220~240V 50Hz)		1.9 A / 300 W	2.9 A / 450 W	3.5 A / 550 W
Rated Input (A/W, 220~240V 60Hz)		2.0 A / 350 W	3.5 A / 600 W	3.5 A / 600 W
Defrosting		Auto		
Certification		CE		



MSM EQUIPMENT MANUFACTURER SDN BHD