

Drop-in Cooker (with Metal Casing)

BKT18



Specification

Electricity	BKT179	220V, 60Hz, 1PH	Power Consumption	BKT179	1800 W
	BKT179(AG)			BKT179(AG)	
	BKT18-A			BKT18-A	
	BKT18-E			BKT18-E	
	BKT18-J			BKT18-J	
Power Connection		Plug type	Max Current		8.5 A
Warming		1 ~ 2 (2 steps)	Heating		3 ~ 8 (6 steps)
Conversion to Calory		1555.2 Kcal/h			
Temperature per Warming Steps	1		2		(1L Water, using chafer)
	35 ℃		60 ℃		
Dimension / Weight		Product: 296 X 370 X 80 (mm) / 4kg Package: 490 X 360 X 170 (mm) / 7.1kg			
Controller Type		Touch screen (integrated into top glass)			
Cookware Diameter		min : Ø130mm max : Ø240mm	Loadable Weight		30 Kg
Recommendation		Hotpot, Shabu shabu, Built-in on dining table			
Functions & Features	■ Metal body makes the unit more durable				
	■ Safety				
	- No vessel : "U" flashing				
	- Over current indication : "1" flashing				
	- Over voltage indication : "2" (Above 265V) flashing				
	- Low voltage : "3" (Below 180V) flashing				
	- Over heated product indication : "4" (IGBT heat sink temperature above 85℃) flashing				
	- Top surface overheated (empty vessel) : "6" (Top surface temperature above 260℃) flashing				
	- Unstable power indication: "7" flashing				
	- Defective PCB indication : "8" flashing				
		- Defective Working Coil indication : "9" flashing			
Warranty		1 year (to be charged in case of user's negligence)			

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.