

Drop-in Cooker (with Metal Casing)

NBK26



Specification

Electricity	NBK26	220V, 60Hz, 1PH			Power Consumption	NBK26		2600 W	
	NBK26-A	208~240V, 50/60Hz, 1PH				NBK26-A			
	NBK26-E	220~240V, 50/60Hz, 1PH				NBK26-E			
	NBK26-CE1	220~240V, 60Hz, 1PH				NBK26-CE1			
	NBK26-J	200V, 50/60Hz, 1PH				NBK26-J		2400 W	
Power Connection		Plug type			Max Current		12 A		
Conversion to Calory		2246.4 Kcal/h							
Warming		H1 ~ H7 (7 steps)			Heating		1 ~ 10 (10 steps)		
Output per Warming Steps		H1	H2	H3	H4	H5	H6	H7	
		40Wh	60Wh	100Wh	130Wh	170Wh	240Wh	350Wh	
Dimension / Weight		Product: 296 X 370 X 80 (mm) / 6.5kg Package: 490 X 360 X 180 (mm) / 7.1kg							
Controller Type		Jog dial, Capacitive button (separated from the unit)							
Power Cable		660 mm			Controller Cable		660 mm		
Cookware Diameter		min : Ø130mm max : Ø240mm			Loadable Weight		30 Kg		
Recommendation		Hotpot, Shabu shabu, Built-in on dining table							
Functions & Features		■ Metal body makes the unit more durable							
		■ Safety							
		- No vessel : "00"							
		- Over current indication : "E1"							
		- Over voltage indication : "E2" (Above 265V)							
		- Low voltage : "E3" (Below 180V)							
		- Over heated product indication : "E4" (IGBT heat sink temperature above 85°C)							
		- Top glass overheated (empty vessel) : "E6" (Top surface temperature above 200°C)							
		- Unstable power indication: "E7"							
		- Defective PCB indication : "E8"							
Warranty		- Defective Working Coil indication : "E9"							
		■ Timer Setting							
		- Between 0sec - 720min (12hr)							
Warranty		1 year (to be charged in case of user's negligence)							

Seoul Office: #75, Ahasan-ro 78-gil, Gwangjin-gu, Seoul, Republic of Korea 04969 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

R&D Center: #209, Goraesan-ro, Wabu-eup, Namyangju-si, Gyeonggi-do, Republic of Korea 12202 / Tel : +82 2-444-5895 / Fax : +82 70-4694-5412

DIPO INDUCTION CO., Ltd. / www.dipoele.com

COPYRIGHT©2010 DIPO INDUCTION CO., LTD ALL RIGHTS RESERVED.