



Vegetable preparation machine CA-601

COMMERCIAL VEGETABLE PROCESSOR WITH AN HOURLY OUTPUT OF UP TO 1000 KG. WITH AUTOMATIC HOPPER.

**2 speed motor block and large production automatic hopper.
3-phase only.
Discs are not included*.**

- Stainless steel construction and high quality material, all suitable for contact with food.
- New production technology that gives a uniform, high-quality cutting result.
- The large range of high quality discs and grids allows the operator to obtain over 70 different styles of product.
- Ergonomic design that allows to cut the product in just one movement.
- Lateral product ejection, reducing the amount of counter space required, whilst also minimising product splashing.
- This directs the product avoiding splashing.
- Electronic, user-friendly control board.
- Easily removable lever and lid for cleaning purposes.
- NSF-International certified appliance (complying with Hygiene, Cleaning and Food Material regulations).

DEFAULT EQUIPMENT

- 2 speed motor block.
- Automatic hopper.

OPTIONAL EQUIPMENT

- Big capacity attachment.
- Long vegetable attachment.
- Stand-trolley.

TECHNICAL SPECIFICATIONS

Hourly production: 500 Kg - 1000 Kg

Inlet opening: 273 cm2

Disc diameter: 205 mm

Total loading: 750 W

Motor speed: 365 rpm / 730 rpm

External dimensions (WxDxH)

Width: 431 mm

Depth: 418 mm

Height: 767 mm

Net weight: 26 Kg

Noise level (1m.): <70 dB(A)

Background noise: 32 dB(A)

AENOR



Empresa Registrada

ER-0437/196



UNE-EN ISO 9001



SAMMIC, S.L.
Basarte, 1 · 20720 AZKOITIA
www.sammic.com

2006/95/EC, 2004/108/EC, NSF/ANSI Standard 8.

EN 60335-1:1997, EN 60335-2-64:93.
UNE-EN 55014:94+A1+A2, UNE-EN 61000-3-2:97+A1+A2+A12.
UNE-EN 61000-3-3:97+C, UNE-EN 55014-2:98.