



## KD120XE

Hood, Decorative wall hood, Classica, Stainless steel, 120 cm, A



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 120 cm • Extraction: Extraction • EAN code: 8017709211646

### AESTHETICS

Colour: Stainless steel • Finishing: Satin • Aesthetics: Classica • Design: Chimney • Material: Stainless steel • Type of steel: Brushed

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### CONTROLS

Control setting: Control knobs • Control knobs: Classic • No. of controls: 2 • Controls colour: Steel effect

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 2 W • Free outlet maximum capacity: 820 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 4 • Anti-grease filters: Stainless steel • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 49 kWh/a • Fluid Dynamic Efficiency (FDE): 32.6 • Lighting Efficiency (LE): 55.5 lux/W • Grease Filtering Efficiency (GFE): 78.7 % • Air flow at minimum speed (Qmin): 332 m<sup>3</sup>/h • Air flow at maximum speed (Qmax): 571 m<sup>3</sup>/h • Air flow at boost speed (Qboost): 794 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 50 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 63 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 71 dB(A) • Time increase factor (F): 0.8 • Energy Efficiency Index: 46.3 • Measured air flow rate at best efficiency point (Qbep): 402 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Pbep): 472 Pa • Measured electric power input at best efficiency point (Wbep): 162 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (Emiddle): 122 lux • Sound power level at highest setting (Lwa): 63 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 278 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1500 mm

## SPEED 1

Extraction rate IEC 61591: 332 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 50 dB(A) • Power: 199 W

## SPEED 2

Extraction rate IEC 61591: 439 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 231 W

## SPEED 3

Extraction rate IEC 61591: 571 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 63 dB(A) • Power: 260 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 794 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 71 dB(A) • Power: 280 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 800x1200x555 • Width: 1200 mm • Depth (mm): 555 mm • Product Height (mm): 800 mm



