

## KSET61

Hood, Integrated hood, Universale, Silver, 60 cm, F



### TYPE

Product family: Hood • Hood Type: Integrated hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709129460

### AESTHETICS

Colour: Silver • Aesthetics: Universale • Design: Telescopic • Material: Painted material

### PROGRAMS / FUNCTIONS

No. of speeds: 2

### CONTROLS

Control setting: Slider

### TECHNICAL FEATURES

No. of lights: 2 • Light type: Incandescent • Light Power: 40 W • Free outlet maximum capacity: 370 m<sup>3</sup>/h • Motor power: 240 W  
• No. of filters: 2 • Anti-grease filters: Aluminium • Vent outlet: 120 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): F • Fluid Dynamic Efficiency class (FDEC): F • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): G • Annual Efficiency Consumption (AEChood): 155 kWh/a • Fluid Dynamic Efficiency (FDE): 6.4 • Lighting Efficiency (LE): 1 lux/W • Grease Filtering Efficiency (GFE): 69.3 % • Air flow at minimum speed (Qmin): 233 m<sup>3</sup>/h • Air flow at maximum speed (Qmax): 332 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 56 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 65 dB(A) • Time increase factor (F): 2.00 • Measured air flow rate at best efficiency point (Qbep): 228 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Pbep): 149 Pa • Measured electric power input at best efficiency point (Wbep): 147 W • Nominal Power consumption of the light system (WL): 80 W • Average illumination of the light on the cooking surface (Emiddle): 52 lux • Sound power level at highest setting (Lwa): 65 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 240 W • Voltage: 220-240 V • Frequency (Hz): 50 Hz • Power supply cable length: 1000 mm

## OPTIONAL ACCESSORIES

### SPEED 1

Extraction rate IEC 61591: 233 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 56 dB(A) • Power: 1 W

### SPEED 2

Extraction rate IEC 61591: 332 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 65 dB(A) • Power: 1 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 208x600x284 • Width: 600 mm • Depth (mm): 284 mm • Product Height (mm): 208 mm

