

Mod. ZO161BA

RF42ILXEHEJ100GF3A

**FUNCTIONS:**

Blast Chilling
Shock Freezing

GENERAL FEATURES:

External sides and top in AISI 304 18/10 stainless steel th. 0,8mm (Scotch-Brite satin finish)
Top in stainless steel th. 1 mm (Scotch-Brite satin)
Inner in stainless steel with rounded corners
Cavity with central drain for discharge of washing water
Heating element in the door frame
Ergonomic full-height door handle

INTERNAL SETUP:

Heated core probe
Pre-cooling function
Automatic storing at end of blast chilling
Removable stainless steel guides, can be positioned by interlocking (GN - EN)

CONTROLS AND SAFETY DEVICES:

Capacitive TOUCH control with 2,8' high definition display placed on the door, easy to use

COOLING SYSTEM:

Condensing unit on board with air cooling
R452A ecological refrigerant fluid
Indirect blowing electronic fans, efficient but gentle on food
Copper-aluminum evaporator with cataphoresis anti-corrosion treatment
High-ventilation evaporator to ensure the highest efficiency of the cooling system
High performance copper-aluminum condenser
Class T (ambient temperature + 43 ° C)

VERSIONS / ACCESSORIES (OPTIONALS):

Bluetooth connection

Mod. **ZO161BA**

RF42ILXEHE100GF3A

MODELLO:		ZO161BA
NET WIDTH	mm	790
NET DEPTH	mm	870
NET HEIGHT	mm	1960
NET WEIGHT	Kg	210
PACKED WIDTH	mm	890
PACKED DEPTH	mm	970
PACKED HEIGHT	mm	2110
PACKED WEIGHT	Kg	250
PACKED VOLUME	m³	1.82
NET HEIGHT DOOR	mm	1130
DOOR OPENING WIDTH	mm	670
INNER DEPTH	mm	450
INSULATION THICKNESS	mm	60
N° OF COMPARTMENTS	n°	1
N° OF DOORS	n°	1
INTERNAL SETUP	Tray holder with double step guides	
POWER SUPPLY	400V-3N+PE 50Hz	
NUMBER OF LOAD POSITIONS	n°	14
PITCH	mm	73
LOADING CAPACITY n° TRAYS GN	n°	28 / 18 / 14
LOADING CAPACITY n° TRAYS EN	n°	28 / 18 / 14
CHILLING CAPACITY	Kg	80
FREEZING CAPACITY	Kg	60
REFRIGERANT	gas	R452A
NOMINAL CURRENT	A	7.79
ABSORBED ELECTRICAL POWER	W	3840
COOLING POWER	W	2724
NOIS LEVEL	dB(A)	67
QUANTITY CHARGE GAS	g	1700
CLIMATE CLASS		5
TEMPERATURE 2	°C	-18
TEMPERATURE	°C	3
YIELD PER CYCLE (+65/+10°C) Kg	[EN17032]	75
YIELD PER CYCLE (+65/-18°C) Kg	[EN17032]	50
Energy cosumption for freezing function	[kWh/Kg]	0.06
Energy cosumption for blast chilling function	[kWh/Kg]	0.19

(*) For mod. BF___Evap. temperature -25°C - Cond. Temperature +40°C

Mod. **ZO161BA**

RF42ILXEHE100GF3A

