

Mod. **ZO122BA**

RF42ILXEJHF100GF3A

**FUNCTIONS:**

Blast Chilling

Shock Freezing

**GENERAL FEATURES:**

External sides and top in AISI 304 18/10 stainless steel th. 0,8mm (Scotch-Brite satin finish)

Top in stainless steel th. 1 mm (Scotch-Brite satin)

Inner in stainless steel with rounded corners

Cavity with central drain for discharge of washing water

Heating element in the door frame

Ergonomic full-height door handle

**INTERNAL SETUP:**

Heated core probe

Pre-cooling function

Automatic storing at end of blast chilling

Removable stainless steel guides, can be positioned by interlocking (GN - EN)

**CONTROLS AND SAFETY DEVICES:**

Capacitive TOUCH control with 2,8' high definition display placed on the door, easy to use

**COOLING SYSTEM:**

Condensing unit on board with air cooling

R452A ecological refrigerant fluid

Indirect blowing electronic fans, efficient but gentle on food

Copper-aluminum evaporator with cataphoresis anti-corrosion treatment

High-ventilation evaporator to ensure the highest efficiency of the cooling system

High performance copper-aluminum condenser

Class T (ambient temperature + 43 ° C)

**VERSIONS / ACCESSORIES (OPTIONALS):**

Bluetooth connection

Mod. **ZO122BA**

RF42ILXEHJF100GF3A

| MODELLO:                                      |                                     | ZO122BA      |
|-----------------------------------------------|-------------------------------------|--------------|
| NET WIDTH                                     | mm                                  | 1100         |
| NET DEPTH                                     | mm                                  | 1080         |
| NET HEIGHT                                    | mm                                  | 1860         |
| NET WEIGHT                                    | Kg                                  | 255          |
| PACKED WIDTH                                  | mm                                  | 1200         |
| PACKED DEPTH                                  | mm                                  | 1180         |
| PACKED HEIGHT                                 | mm                                  | 2010         |
| PACKED WEIGHT                                 | Kg                                  | 295          |
| PACKED VOLUME                                 | m³                                  | 2.85         |
| NET HEIGHT DOOR                               | mm                                  | 880          |
| DOOR OPENING WIDTH                            | mm                                  | 670          |
| INNER DEPTH                                   | mm                                  | 930          |
| INSULATION THICKNESS                          | mm                                  | 60           |
| N° OF COMPARTMENTS                            | n°                                  | 1            |
| N° OF DOORS                                   | n°                                  | 1            |
| INTERNAL SETUP                                | Tray holder with double step guides |              |
| POWER SUPPLY                                  | 400V-3N+PE 50Hz                     |              |
| NUMBER OF LOAD POSITIONS                      | n°                                  | 11           |
| PITCH                                         | mm                                  | 75           |
| LOADING CAPACITY n° TRAYS GN                  | n°                                  | 44 / 28 / 22 |
| LOADING CAPACITY n° TRAYS EN                  | n°                                  | 44 / 28 / 22 |
| CHILLING CAPACITY                             | Kg                                  | 80           |
| FREEZING CAPACITY                             | Kg                                  | 55           |
| REFRIGERANT                                   | gas                                 | R452A        |
| NOMINAL CURRENT                               | A                                   | 8.85         |
| ABSORBED ELECTRICAL POWER                     | W                                   | 4740         |
| COOLING POWER                                 | W                                   | 3307         |
| NOIS LEVEL                                    | dB(A)                               | <70          |
| QUANTITY CHARGE GAS                           | g                                   | 2300         |
| CLIMATE CLASS                                 |                                     | 5            |
| TEMPERATURE 2                                 | °C                                  | -18          |
| TEMPERATURE                                   | °C                                  | 3            |
| YIELD PER CYCLE (+65/+10°C) Kg                | [EN17032]                           | 80           |
| YIELD PER CYCLE (+65/-18°C) Kg                | [EN17032]                           | 55           |
| Energy cosumption for freezing function       | [kWh/Kg]                            | 0.07         |
| Energy cosumption for blast chilling function | [kWh/Kg]                            | 0.18         |

(\*) For mod. BF\_\_Evap. temperature -25°C - Cond. Temperature +40°C

Mod. **ZO122BA**

RF42ILXEHJF100GF3A

