

# **High Speed Oven**

Project	
Item	
Quantity	
CSI Section 11400	
Approval	
Date	

# Merrychef eikon<sup>®</sup> e1s




### Standard Features

- Rapid Cooking Technology combines three heat technologies:
  - Tuned Impingement
  - Microwave
  - Convection
- Ventless cooking capabilities through built-in catalytic converter
- Rapid cooking up to 10-12 times faster than a conventional oven
- 31cm x 31cm (12" x 12") cavity in a 41cm (16") width footprint
- Cool-to-touch exterior
- easyTouch®, icon driven touchscreen user interface
- Very easy to clean with large rounded • edges
- Quiet operation 52 dbA in standby mode .
- USB memory stick data transfer of up to 1024 cooking profiles
- Built-in diagnostic testing
- Fits on a 50cm (19.7") worktop and no need for side installation space
- Black exterior on stainless steel
- Soft edge front design

## Accessories

- Solid cook plate
- Cook plate liner
- Guarded paddle with supporting side walls
- Solid base basket
- Other accessories by request

**Specifications** 



#### How it Works

The convection fan pulls air in through the fan inlet (1). This is then heated and returned to the cavity through the catalytic converters (2) and impinger plate (3) to produce an even heat pattern in the oven. This heat pattern allows food to cook evenly and produces a crisp golden finish, everytime.

Welbilt UK Limited,

Ashbourne House, The Guildway,

Old Portsmouth Road,

Guildford, GU3 1LR, United Kingdom

Tel: +44(0)1483 464900 昌 Fax: +44(0)1483 464905 www.welbilt.com www.merrychef.com

VELBILT

E



#### **INCLUDED ACCESSORIES**

- Reversible solid and griddle cook plate
- Paddle with supporting side walls
- Cook plate liner
- Solid base basket

#### CONSTRUCTION

• Stainless steel cavity and casework (painted)


#### **MICROWAVE POWER**

Microwave settings, off or 5–100% in 1% increments

#### CONVECTED HEAT

•

 Temperature settings OFF and from 100°C to 260° C / 212°F to 500°F in 1°C steps



#### DIMENSIONS

MODEL	OVERALL SIZE			
WODEL	HEIGHT	WIDTH	DEPTH	WEIGHT
eikon <sup>®</sup> e1s Classic	588 mm 407 mm (23.2") (16.0")		538 mm (21.2")	NET 46.0 kg (101 lbs) GROSS 56.0 kg (124 lbs)

#### **POWER REQUIREMENTS & OUTPUT**


#### Merrychef eikon e1s

Country / Region (examples)	Voltage	Arrangement	Connections Used	Plug Current Rating per Phase*	Max. Power Input	Microwave** (IEC 705) 100%	Convected Heat	Combination Mode
AP	1N~ 200-230 V 50 Hz	Single phase	L + N + E	16 A	2990 W	800 W	2200 W	800 W** + 900 W
KR	1N~ 208-240 V 60 Hz	Single phase	L + N + E	16 A	2990 W	800 W	2200 W	800 W** + 900 W
CN	1N~ 200-230 V 50 Hz	Single phase	L + N + E	15 A	2990 W	800 W	2200 W	800 W** + 900 W
PH	1N~ 208-240 V 60 Hz	Single phase	L + N + E	15 A	2990 W	800 W	2200 W	800 W** + 900 W
TW	1N~ 208-240 V 60 Hz	Single phase	L + N + E	15 A	2990 W	800 W	2200 W	800 W** + 900 W
IN	2N~ 380-400 V 50 Hz	Twin phase	L1 + L2 + N + E	16 A	2990 W	800 W	2200 W	800 W** + 900 W

Welbilt reserves the right to make the changes to the design or specifications without prior notice.

#### Welbilt UK Limited,

Ashbourne House, The Guildway, Old Portsmouth Road, Guildford, GU3 1LR, United Kingdom



www.welbilt.com www.merrychef.com