

DOOR TYPE DISHWASHER

STANDARD

POWER

POWERFUL washing standards.
Sustained pressure to deliver extraordinary results. Selectable wash timing. Stainless steel impellers housing.



DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. **ENDURING** performance with zero-trouble experience.



DYNAMIC

Electrical components are not affected by the different environment and kitchen settings it is put into. It delivers **CONSISTENT** results everywhere.



Technical Data

Model: GT-D1M (TC-RB)

GT-D1M (LE-RB)

Dimensions (mm): 697 (W) x 683 (D) x 1620 (H)

697 (W) x 683 (D) x 1620 (H)

Loading Height (mm): 420

420

Power Supply: 415V/50Hz 3 Phase

230V/50Hz 1 Phase

Electrical Loading: 11 kW | 15 A (Alternative Heating)
14 kW | 20 A (Full Heating)

3.5 kW | 15 A (Alternative Heating)
5.5 kW | 24 A (Full Heating)

Wash Tank Heater: 3 kW

2 kW

Booster Tank Heater: 9 kW

2 kW

Wash Pump: 0.95 kW

0.95 kW

Rinse Pump: 0.25 kW

0.25 kW

Wash Cycle (Per Rack) 60 or 90 sec (selectable)

70 or 100 sec (selectable)

Rinse Usage: <2.4 liters per cycle

<2.4 Liters per cycle

Wash Tank Capacity: 36 liters

36 liters

Booster Tank Capacity: 10 liters

10 liters

Machine Net Weight: 128 kg

128 kg

