

UNDER COUNTER DISH WASHER

STANDARD


FORM

The Standard variant **FORM** an excellent solution in glass and dishwashing for micro dining setting. Its compact and sturdy build gives it a convenient means to be placed anywhere in the kitchen or bar.




FIT

Compact build makes it easy to **FIT** into your kitchen. It has simple access to maintenance and servicing, saving chunks of time for the technical team.



FUNCTION

Electrical parts **FUNCTION** collaboratively in our design system architecture. Mechanical system design that is universal across our machines, intricately engineered from our design and engineering department.



Technical Data

Model:	GT-U1M (C)	GT-U1M (C)
Dimensions (mm):	600 (W) x 607 (D) x 751~771 (H)	600 (W) x 607 (D) x 751~771 (H)
Loading Height (mm):	310	310
Power Supply:	415V/50Hz 3 Phase	230V/50Hz 1 Phase
Electrical Loading:	5.5kW (12A)	5.5kW (24A)
Wash Tank Heater:	3kW	3kW
Booster Tank Heater:	4.5kW	4.5kW
Wash Pump:	0.62kW	0.62kW
Rinse Pump:	NA	NA
Wash Cycle (Per Rack):	90 sec	90 sec
Rinse Usage:	<2.1 liters per cycle	<2.1 liters per cycle

