



Model No.	External (mm) W*D*H	Capacity (L)	Operating Temp. (°C)	Rated(V) Current(A)	No. of shelves	Weight NW./GW.	Shipping dimension mm
CRA-120-N-SD	1200×760×850	290	2~6	220V/2.6	2	95/105 kgs	1290*820*890
CRA-150-N-SD	1500×760×850	380	2~6	220V/2.8	2	109/119 kgs	1590*820*890
CRA-180-N-SD	1800×760×850	480	2~6	220V/2.8	2	131/142 kgs	1890*820*890

CFA-120-N-SD	1200×760×850	290	-14~-18	220V/3.5	2	97/107 kgs	1290*820*890
CFA-150-N-SD	1500×760×850	380	-14~-18	220V/4.6	2	112/122 kgs	1590*820*890
CFA-180-N-SD	1800×760×850	480	-14~-18	220V/4.6	2	133/145 kgs	1890*820*890

FEATURES:

- Fan forced evaporator cooling.
- Self-contained refrigeration system in the right side.
- Automatic evaporation of the defrost water by using the high pressure hot gas of the copper pipe.
- High quality international brand compressor: Embraco aspera compressor.
- The reduced dimension of compressor section provides a bigger inside space of the counter.
- Waterproof control panel easy to read and control.
- Door construction for compressor section for easy maintenance.
- Wide magnetic gasket gives effective seal and is removable for easy cleaning and maintenance.
- Self closing doors with locks.

OPTION

- Stainless steel splash-back to prevent spillage behind the counter.
- Standard stainless steel bullet feet, adjustable from 135 to 165mm, castors with 130mm height is optional.
- Left compressor section.