



Electrolux

ecostore 2 Door Digital Stainless Steel Freezer, 1430lt (-22/-15)

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



727297 (RE4142FF)

Eco Store Stainless Steel
Freezer - 1430 lt 2 Door
(-22/-15) - 230 V/1N/50Hz

727437 (RE4142FF60)

Eco Store Stainless Steel
Freezer - 1430 lt 2 Door
(-22/-15) - 220 V/1N/60Hz

Short Form Specification

Item No. _____

Two full door freezer with internal and external structure in 430 AISI stainless steel; external back panel in galvanized steel and bottom panel in anti-corrosive material. Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms. Optimized back to front forced air flow provides even temperature distribution and fast cooling in any conditions. Fitted with 75 mm-thick cyclopentane insulating foam. Door features lock and door microswitch to switch off the fan when the door is opened. Hidden evaporator to guarantee higher storage capacity and less corrosion problems. Built-in refrigeration unit; ventilated operation; automatic defrost and evaporation of defrost water. For ambient temperatures up to 43 °C. CFC and HCFC free. R404a gas in refrigeration circuit. Supplied with n. 6x2/1GN Rilsan coated grids and n. 6 sets of 2 stainless steel grid runners.

Main Features

- Two full doors.
- Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Optimized back to front forced air flow provide even temperature distribution and fast cooling in any conditions.
- Automatic defrost.
- Internal structure with numerous charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating performance with 100% environmental protection (thermal conductivity: 0,020 W/m*K).
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- 60 mm-thick insulation covering the evaporator can be easily removed with a single operation.
- Rilsan coated grids for improved protection.
- Hidden evaporator thus guaranteeing higher storage capacity and less corrosion problems.
- Tropicalized unit (43°C ambient temperature). (only for 727297)
- This appliance is intended for use in ambient temperatures up to 40°C. (only for 727297)
- Freezer model has operating temperatures that can be adjusted from -22 to -15 °C.

Construction

- Interior base with corners, pressed from a single sheet.
- External back panel in galvanized steel.
- Stainless steel runners and supports easily disassembled.
- Anti-corrosion bottom avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.
- Lockable door.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- Refrigerant type: R404a.
- CFC and HCFC-free insulation.
- Doors are self-closing and can be fully opened up to 180°.
- Mounted on adjustable Stainless steel feet, with castors as an option.
- The rounded internal corners, the easily removable runners and grids allow for ease of cleaning and high hygiene standards.
- AISI 430 stainless steel internal structure and external panels.

APPROVAL: _____



Electrolux

2 Door Digital Stainless Steel Freezer, 1430lt (-22/-15) **ecostore**

- Easy access to the main components for maintenance.
- Delivered with UK plug. (only for 727437)



Electrolux

ecostore
2 Door Digital Stainless Steel
Freezer, 1430lt (-22/-15)

Included Accessories

- 6 of 2/1GN grey rilsan grid with 2 runners PNC 881020

Optional Accessories

- 2 stainless steel runners for refrigerated cabinets - (Marine) PNC 880242 ☐
- Set of 8 GN1/1 PVC containers for fish (only for 727297) PNC 880243 ☐
- Spacer for 670 lt and 1430 lt refrigerated cabinets PNC 880248 ☐
- Kit integrated HACCP for digital refrigerators (IR33) PNC 880252 ☐
- - NOT TRANSLATED - PNC 880333 ☐
- Kit of 6 swivelling wheels, 2 with brake, diam 50 mm PNC 880340 ☐
- 1/1GN plastic container with false bottom PNC 880705 ☐
- 4 swivelling wheels (2 with brake) for refrigerators, diam 125 mm, NOT for Glass Door and remote models PNC 881002 ☐
- 2/1GN grey rilsan grid PNC 881004 ☐
- 2/1GN aisi 304 stainless steel grid PNC 881016 ☐
- 2/1GN 304 AISI stainless steel grid with 2 runners PNC 881018 ☐
- 2/1GN grey rilsan grid with 2 runners PNC 881020 ☐
- Set of 2 stainless steel runners for 670/1430lt refrigerators and freezers PNC 881021 ☐
- Pedal opening for 1430lt refrigerator PNC 881033 ☐
- 2/1GN pvc container with lid and 2 runners PNC 881039 ☐
- 2/1GN perforated shelf PNC 881042 ☐
- 1/1GN rilsan steel wire basket h=150mm PNC 881043 ☐
- 3 grey rilsan central grids for 1430lt (not for glass door) PNC 881044 ☐
- 2/1GN grey rilsan basket+2 runners h=150mm PNC 881047 ☐



ecostore
2 Door Digital Stainless Steel Freezer, 1430lt (-22/-15)


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

9/19 2018.08.28




Electrolux

ecostore
2 Door Digital Stainless Steel
Freezer, 1430lt (-22/-15)




Front



Side

EI = Electrical connection
RI = Refrigerant Inlet
RO = Remote unit connection



Top

Electric

Supply voltage:	
727297 (RE4142FF)	220-230 V/1 ph/50 Hz
727437 (RE4142FF60)	220 V/1 ph/60 Hz
Electrical power, max:	
727297 (RE4142FF)	0.83 kW
727437 (RE4142FF60)	0.766 kW

Key Information:

Gross capacity:	1430 lt
Net Volume:	
727297 (RE4142FF)	1135 lt
727437 (RE4142FF60)	1025 lt
Door hinges:	1 Left+1 Right
External dimensions, Width:	1441 mm
External dimensions, Height:	2050 mm
External dimensions, Depth:	835 mm
External dimensions, Depth with Doors Open:	1480 mm
Number and type of doors:	2 Full
Number and type of grids (included):	6 - GN 2/1
Type of external material:	Stainless Steel
Type of internal material:	Stainless Steel
Internal panels material:	Stainless Steel
Number of positions & pitch:	44; 30 mm

Refrigeration Data

Control type:	Digital
Refrigerant type:	R404a
Refrigeration power:	
727297 (RE4142FF)	751 W
727437 (RE4142FF60)	777 W
Refrigeration power at evaporation temperature:	-30 °C
Refrigerant weight:	290 g
Operating temperature min.:	-22 °C
Operating temperature max.:	-15 °C
Operating mode:	Ventilated

Product Information (EU Regulation 2015/1094)

Energy Class:	
727297 (RE4142FF)	E
727437 (RE4142FF60)	0
Yearly energy consumption:	
727297 (RE4142FF)	5577kWh/year - 15.28kWh/24h
Climate class:	
727297 (RE4142FF)	Heavy Duty (5)
Energy Efficiency Index (EEI):	
727297 (RE4142FF)	78,93
727437 (RE4142FF60)	0
[NOT TRANSLATED]	
727297 (RE4142FF)	vertical frozen



ecostore
2 Door Digital Stainless Steel Freezer, 1430lt (-22/-15)


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



Electrolux

ecostore
2 Door Digital Stainless Steel
Freezer, 1430lt (-22/-15)

EnergyLabel



ecostore
2 Door Digital Stainless Steel Freezer, 1430lt (-22/-15)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

11/19018.08.28