Digital Cabinets Benefit - 4 Half Doors Digital Freezer, Stainless Steel - 1300 It

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



790003 (SB130F4D)

Benefit Digital 4 Half Door Freezer, Stainless Steel -1300 It - 230 V/1N/50Hz

790047 (SB130F4D6)

Benefit Digital 4 Half Door Freezer, Stainless Steel -1300 lt - 220 V/1N/60Hz

Short Form Specification

Item No.

Internal structure in 304 AISI stainless steel. External panels in stainless steel. High-density expanded polyurethane insulating foam, 60mm in thickness. Lockable doors with closure latch and microswitch to switch off the fan when the door is opened. Built-in refrigeration unit; ventilated operating mode; digital control; automatic defrost and evaporation of defrost water; external digital temperature display. For ambient temperatures up to 38° C. CFC and HCFC free. R404a gas in refrigeration circuit. Supplied with n. 8x2/1GN nylon coated grids and n. 8 sets of 2 stainless steel grid runners.

Main Features

- IP65 digital control panel allows for temperature and parameter setting as well as to activate defrosting when necessary.
- The digital control features service and HACCP alarms and can be connected to a remote computer.
- Freezer model has operating temperatures that can be adjusted from -22 to -15 °C.
- Forced air circulation for rapid cooling and an even temperature distribution.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Lockable door with closure latch.
- Automatic evaporation of defrost water.
- Door frame heater, activated according to external temperature, avoids condensation build-up around the door frame.

Construction

- Internal structure in AISI 304 stainless steel and external structure in AISI 430 stainless steel as standard.
- Easy to clean, reversible self-closing door with baloon profile, magnetic door seal to guarantee perfect closure.
- The rounded internal corners, the easily removable runners and grids allow for ease of cleaning and high hygiene standards.
- High density polyurethane insulation, 60 mm tickness, HCFC free.
- CFC and HCFC-free insulation.
- Refrigerant type: R404a.
- Built-in compressor to suit operating conditions.
- Mounted on 150 mm adjustable feet.
- Electronic protection against high voltage peaks.
- Coated evaporator to avoid corrosion and to guarantee everlasting operation.
- Back panel in galvanized steel.

Included Accessories

 8 of Kit of 1x2/1GN PVC grids with side runners for 600/1300lt retrigerated cabinets

Optional Accessories

• Kit of 4 low feet for cabinets

PNC 880264 □

 Kit of 1x2/1GN PVC grids with side runners for 600/1300lt retrigerated cabinets

PNC 880297 □

APPROVAL:






Digital Cabinets Benefit - 4 Half Doors Digital Freezer, Stainless Steel - 1300 It


•	4 central PVC grids for 1300lt refrigerated cabinets	PNC 880298 □
	Kit of 5 wheels (front with brake) for cabinets and counters	PNC 880301 □






Digital Cabinets Benefit - 4 Half Doors Digital Freezer, Stainless Steel - 1300 It





EI = Electrical inlet (power) RI = Refrigerant Inlet RO = Refrigerant Outlet



DNV-GL #6

Electric

Supply voltage: 790003 (SB130F4D)

790003 (SB130F4D) 220-230 V/1 ph/50 Hz 790047 (SB130F4D6) 220 V/1 ph/60 Hz

Electrical power max.: 0.95 kW

Key Information:

Gross capacity:

1300 lt

Door hinges:

External dimensions, Width: 1440 mm External dimensions, Height: 2000 mm External dimensions, Depth: 788 mm

External dimensions, Depth with Doors Open:

1450 mm

Number and type of doors: Number and type of grids 4x1/2 Full

(included):

Type of external material:

8 - GN 2/1 Stainless Steel

Stainless Steel AISI 304

Type of internal material: Number of positions & pitch: Scotch Brite 0; 0 mm

Refrigeration Data

Compressor power: 1 hp
Refrigerant type: R404A
Operating temperature min.: -22 °C
Operating temperature max.: -15 °C
Operating mode: Ventilated
Cooling unit: Built-In
Defrost type: Electric

Digital Cabinets Benefit - 4 Half Doors Digital Freezer, Stainless Steel - 1300 lt